## **CLAIMS**

## What is claimed is:

- 1. A method of controlling a cryopump, the method comprising:
- setting an identifier when a temperature is below an operational set point;

if an identifier has been set, responding to a temperature that is above a warmup set point by directing a purge valve to open.

A method of controlling a cryopump as in Claim 1 wherein directing a purge
 valve to open includes at least one of:

causing a cryo-purge valve coupled to the cryopump to open; and causing an exhaust purge valve coupled to an exhaust line of the cryopump to open.

- 3. A method of controlling a cryopump as in Claim 1 wherein the operational set point is 18K.
  - 4. A method of controlling a cryopump as in Claim 1 wherein the warmup set point is above 34K.
- A method of controlling a cryopump as in Claim 1 wherein causing a purge
   valve to comprises delivering purge gas into the cryopump without initiating an entire regeneration process.
  - 6. A cryopump controller which is programed with instructions for:
    setting an identifier when a temperature is below an operational set point;
    and

if an identifier has been set, responding to a temperature that is above a warmup set point by directing a purge valve to open.

- A cryopump controller as in Claim 6 wherein the instructions for directing a
   purge valve to open include instructions for at least one of:
   causing a cryo-purge valve coupled to the cryopump to open; and
   causing an exhaust purge valve coupled to an exhaust line of the
  - 8. A cryopump controller as in Claim 6 wherein the operational set point is 18K.
- 10 9. A cryopump controller as in Claim 6 wherein the warmup set point is above 34K.
  - 10. A cryopump controller as in Claim 6 wherein directing a purge valve to open comprises delivering purge gas into the cryopump without initiating an entire regeneration process.
  - 11. A cryopump comprising:

15

20

cryopump to open.

a controller in communication with the cryopump, the controller including instructions for:

setting an identifier when a temperature is below an operational set point; and

if an identifier has been set, responding to a temperature that is above a warmup set point by directing a purge valve to open.

- 12. A cryopump as in Claim 11 wherein the instructions for directing a purge valve to open include instructions for at least one of:
- causing a cryo-purge valve coupled to the cryopump to open; and

causing an exhaust purge valve coupled to an exhaust line of the cryopump to open.

- 13. A cryopump as in Claim 11 wherein the operational set point is 18K.
- 14. A cryopump as in Claim 11 wherein the warmup set point is above 34K.

5

- 15. A cryopump as in Claim 11 wherein directing a purge valve to open comprises delivering purge gas into the cryopump without entering into an entire regeneration process.
- 10 16. A system for controlling a cryopump, the system comprising:

a means for setting an identifier when a temperature is below an operational set point; and

a means for responding to a temperature that is above a warmup set point by directing a purge valve to open when an identifier has been set.

15